

329 0% MERCURY

SR731SW Watch Battery OEM Swiss Made

Technical Data Sheet

Specifications

Chemical system Zinc / Monovalent Silver Oxide, low drain

Nominal Voltage 1,55 V

Capacity 37 mAh, Discharge over 25,5 kΩ at 20°C to 1,2 V

Operating Temperature* -10°C – 60°C


Self Discharge Less than 5% per year at 20°C

Weight ~0,58 g

Dimensions

(according IEC 60086-3)

Diameter 7,90 mm (0,311") Height 3,10 mm (0,122")



Discharge Curve

 $\begin{array}{ll} \text{Constant Load} & 25,5 \text{ k}\Omega \\ \text{Starting Drain} & 61,2 \text{ } \mu\text{A} \\ \text{Temperature} & 20 ^{\circ}\text{C} \end{array}$

1.5 9 bet 1.4 1.3 1.2 1.1 0 100 200 300 400 500 Time [h]

*Condensing humidity not allowed

Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative. For safety related information please consult the PSDS document related to that product or product family. The Products of Renata SA are neither designed nor authorized for use in certain areas of application of environment. For further details we refer to our webpage www.renata.com/downloads/restriction_of_use

1.7 1.6

Rev. 329MF_OEM.05 2019/08

700

600